



Friedhelm TRAPP GmbH

Ostring 15 - 63533 Mainhausen - Zentrale: 06182/9294-5 - Fax: 06182/9294-69 - Mail: trapp@f-trapp.de

www.f-trapp.de

LED-Hanging luminaire A-11 HPower



Hanging luminaire 9-fl. LED 80 W - His.lux® warmwhite

The robust LED hanging luminaire made of aluminum and stainless steel corresponds in shape and design of the gas hanging luminaire A 11.

This lamp is characterized by a high efficiency of the cooling system and the rugged, powerful LED engine.

Technical description

- Shutdown and / or dimming of the two LED groups is possible
- Dimming is based on switching on or off of a 230V / 50Hz phase
- The performance of the lamp is adjustable in 10 Steps
- The power reduction (HNS) is adjustable in 10 Steps
- A fading (smooth change) to the half night switching is integrated
- All electronic components are protected from moisture
- The power supply has an All-Around Protection: OVP, SCP, OLP and SELV
- Service-friendly by individually replaceable LED lamps



Friedhelm TRAPP GmbH

Ostring 15 - 63533 Mainhausen - Zentrale: 06182/9294-5 - Fax: 06182/9294-69 - Mail: trapp@f-trapp.de

www.f-trapp.de

LED-Hanging luminaire A-11 HPower

Special technical information:

| | |
|---------------------------|--|
| Operating voltage: | 230 VAC/50Hz |
| Power consumption: | max.: 77,3 Watt / manually adjustable |
| Luminous flux: | 4729 Lumen / Lumen Maintenance L70/B10 |
| Light color: | 2840 K |
| System luminous efficacy: | 61,17 lm/W |
| ULOR: | 2,58% |
| Power factor: | 0,97 |
| Protection grade: | IP54 luminaire / LED space IP68 / IP68 LED bulbs |
| Power Supply: | firm Inventronics type:.. Governed EUC 026S035DS / SELV, electronic (CE / TÜV / ENEC / RoHs) |
| Protectionclass: | SK II |
| Ambient temperature: | -40°C bis 50°C |
| Luminaire glass: | Polycarbonate clear |
| Mounting: | 1 Zoll outer thread V2A |
| Dimensions: | Diameter 460 mm, height 760 mm |
| Windage area: | 0,3563m ² |
| Wind drag coefficient: | 1,2 |
| Weigh: | approx. 8 kg |